



imagePRESS V1000

COLOR PRODUCTION
DIGITAL PRESS



imagePRESS V1000 shown with optional accessories.

Product Specifications

Marking Engine

Technology	Electrophotography	
Print Speed	8.5" x 11":	Up to 101 ipm
	11" x 17":	Up to 52 ipm
	12" x 18":	Up to 50 ipm
	13" x 19":	Up to 48 ipm
	13" x 30":	Up to 28 ipm
Paper Size	Standard:	3.9" x 5.8" to 13" x 19.2"
	Optional:	5.5" x 7.2" to 13" x 51.2"
Paper Capacity¹	Standard:	Up to 1,100 Sheets
	Optional:	Up to 11,100 Sheets
Paper Weight	Standard:	14 lb. Bond to 110 lb. Cover (52 gsm to 300 gsm)
	Optional:	14 lb. Bond to 150 lb. Cover (52 gsm to 400 gsm)
	Envelopes:²	No. 10, ISO-C5, DL, Monarch, 6" x 9", 9" x 12", 10" x 13"
Automatic Duplexing	Paper Size:	Up to 13" x 51.2" ³
	Paper Weight:	Up to 150 lb. Cover ⁴ (400 gsm)
Power Source	(2) Single-Phase 200 -240 V, 50/60 Hz, 20 A	
Weight	904 lb.	
Dimensions	62.3" W x 34.3" D x 40.9" H	

Input Accessories

Multi-Drawer Paper Deck-E1	Paper Capacity:¹	Up to 5,000 Sheets
	Paper Size:	5.5" x 7.2" to 13" x 19.2"
	Paper Weight	
	Top/Middle:	14 lb. Bond to 130 lb. Cover (52 gsm to 350 gsm)
	Bottom:	14 lb. Bond to 150 lb. Cover (52 gsm to 400 gsm)
	Power Source:	110 – 127 V, 60 Hz, 7 A
	Weight:	392 lb.
	Dimensions:	38" W x 31.5" D x 42.5" H
POD Deck Lite-C1	Paper Capacity:¹	Up to 3,500 Sheets
	Paper Size:	5.5" x 5.8" to 13" x 19.2"
	Paper Weight:	14 lb. Bond to 150 lb. Cover (52 gsm to 400 gsm)
	Power Source:	120 – 127 V, 60 Hz, 2.2 A
	Weight:	168 lb.
	Dimensions:	28.2" W x 27" D x 22.6" H
POD Deck Lite XL-A2	Paper Capacity¹	
	Up to 13" x 19.2":	Up to 3,500 Sheets
	Up to 13" x 30":	Up to 1,000 Sheets
	Paper Size:	5.5" x 5.83" to 13" x 30"
	Paper Weight:	
	Up to 13" x 19.2":	14 lb. Bond to 150 lb. Cover (52 gsm to 400 gsm)
	Up to 13" x 30":	14 lb. Bond to 110 lb. Cover (52 gsm to 300 gsm)
	Power Source:	120 – 127 V, 60 Hz, 2.2 A
	Weight:	249 lb.
	Dimensions:	43.5" W x 27" D x 22.6" H

Input Accessories (Continued):

Stack Bypass-D1	Paper Capacity: ¹	Up to 250 Sheets
	Paper Size:	3.9" x 5.83" to 13" x 19.2"
	Paper Weight:	14 lb. Bond to 130 lb. Cover (52 gsm to 350 gsm)
	Weight:	3 lb.
	Dimensions:	18" W x 15.1" D x 2.9" H
Long Sheet Feeding and Catch Tray-B1	Paper Capacity:	Up to 1 Sheet
	Paper Size:	8.3" x 19.2" to 13" x 51.2"
	Paper Weight:	14 lb. Bond to 110 lb. Cover (52 gsm to 300 gsm)
	Weight:	2 lb.
	Dimensions:	24.9" W x 56.1" D x 56.1" H
Duplex Color Image Reader-P1	Image Sensor:	CCD
	Scan Speed:	Up to 270 opm (Letter, 300 dpi)
	Document Size:	2.8" x 5.5" to 12" x 24.8"
	Resolution:	Up to 600 x 600 dpi, 256 Gradations
	Tray Capacity: ¹	Up to 200 Sheets
	Weight:	51 lb.
	Dimensions:	25.7" W x 23.3" D x 8.6" H

Finishing Accessories

Sensing Unit-B1⁵	Tasks:	Front-to-Back Alignment, Color Accuracy Check, Cross Shade Adjustment, Secondary Transfer Adjustment
	DfE:	PRISMAsync print server V8.3 or Later; imagePRESS Server D3000 V1.0 or Later
	Paper Weight:	14 lb. Bond to 150 lb. Cover (52 gsm to 400 gsm)
	Paper Size:	5.5" x 5.83" to 13" x 51.2"
	Power Supply:	100 – 240 V, 50/60 Hz, 2.5 A
	Weight:	222 lb.
	Dimensions:	20.3" W x 29.5" D x 48.3" H
Inspection Unit-A1⁵	Paper Type:	Plain Paper, Coated Paper
	Paper Weight:	14 lb. Bond to 150 lb. Cover (52 gsm to 400 gsm)
	Paper Size:	3.9" x 7.2" to 11.9" x 19.2"
	Detection Size:	0.2 mm x 0.2 mm to 1.4 mm x 1.4 mm
	Scanning Width:	Up to 11.9"
	Inspection Workstation	
	Inspection Tool OS:	Windows® 10 Pro
	Mode:	Log Only Mode, Purge and Recovery Mode
	Inspection Location:	Up to 64
	Intensity Level:	9 Levels
	Objects:	Position Gap, Dot of Dirt, Streak of Dirt
	Auto Recovery:	Yes (Purge and Recovery Mode Only)
	Purge Unit:	High Capacity Stacker-J1
	Power Supply:	120 – 240 V, 50/60 Hz, 1.4 A
	Weight:	109 lb.
	Dimensions:	9.8" W x 31.2" D x 40.9" H

Document Insertion Unit-R1⁵	Tray Capacity: ¹	
	Upper Tray:	Up to 200 Sheets
	Lower Tray:	Up to 200 Sheets
	Paper Weight:	14 lb. Bond to 110 lb. Cover (52 gsm to 300 gsm)
	Paper Size:	7.2" x 7.2" to 13" x 19.2"
	Power Supply:	100 – 240 V, 50/60 Hz, 1.4 A
Multi Function Professional Puncher-C1⁵	Weight:	135 lb.
	Dimensions:	29.4" W x 31.2" D x 55.4" H
	Paper Weight	
	Punching:	20 lb. Bond to 110 lb. Cover (75 gsm to 300 gsm)
	Creasing:	110 lb. Text to 110 lb. Cover (157 gsm to 300 gsm)
	Paper Size	
	Punching:	12" x 18", 11" x 17", Letter, Legal, Letter-R, Statement
	Creasing:	Letter-R, 11" x 17", 12" x 18", 13" x 19"
	Die Set Patterns:	Loose-Leaf 3-Hole/5-Hole, Velo Bind 11-Hole, Plastic Comb 19-Hole, Twin Loop 21-Hole/32-Hole, Color Coil 44-Hole, Crease
	Power Supply:	115 V, 60 Hz, 3.8 A
GBC eWire Pro⁷	Weight:	225 lb.
	Dimensions:	17.5" W x 31.3" D x 40.9" H
	Bound Book Size: ¹	7 to 100 Sheets
	Paper Size:	Letter, 5.5" x 8.5", Tab Stock
	Paper Weight:	20 lb. Bond to 110 lb. Cover (75 gsm to 300 gsm)
	Wire Choices:	1/4", 5/16", 3/8", 7/16", 1/2", 9/16"
Perfect Binder-F1⁵	Stack Capacity:	Up to 35 Books
	Power Supply:	115 V, 60 Hz, 2.8A
	Weight:	500 lb.
	Dimensions:	35.8" W x 31.3" D x 42.6" H
	Finished Book Size:	5.4" x 8" to 8.5" x 11.7"
	Book Thickness: ¹	10 to 200 Sheets (Up to 0.98")
Trimming Method:	Body Paper Weight:	14 lb. Bond to 43 lb. Bond (52 gsm to 163 gsm)
	Cover Paper Weight:	24 lb. Bond to 110 lb. Cover (90 gsm to 300 gsm)
	Trim Range	
	Top/Bottom:	0.26" to 1.6"
	Side:	0.26" to 1.95"
	Power Source:	208 V, 60 Hz, 3 A
	Weight:	679 lb.
	Dimensions:	36.3" W x 31.1" D x 51.2" H

Finishing Accessories (Continued):

High Capacity Stacker-J1	Stack Capacity: ¹	Up to 6,000 Sheets
	Top Tray Capacity: ¹	Up to 200 Sheets
	Paper Size:	5.5" x 7.2" to 13" x 19.2"
	Paper Weight:	14 lb. Bond to 150 lb. Cover (52 gsm to 400 gsm)
	Power Source:	100 – 240 V, 50/60 Hz, 2.5 A
	Weight:	265 lb.
	Dimensions:	35.4" W x 29.3" D x 44.9" H

Plockmatic Multi Purpose Stacker⁸	Stack Height	
	Sheets < 25.6":	Up to 11.8"
	Sheets > 25.6":	Up to 5.3"
	Paper Size:	8.3" x 11" to 13" x 30"
	Paper Weight:	100 lb. Text to 130 lb. Cover (148 gsm to 350 gsm)
	Power Source:	100 – 240 V, 50/60 Hz, 2 A
	Weight:	168 lb.
	Dimensions:	41.8" W x 35.4" D x 26.8" H

Paper Folding Unit-K1⁹	Double Parallel Fold:	Legal, Letter-R
	C/Accordion Fold:	Letter-R
	Z-Fold:	Letter-R, 11" x 17"
	Paper Weight:	14 lb. Bond to 28 lb. Bond (52 gsm to 105 gsm)
	Power Source:	From Finisher
	Weight:	157 lb.
	Dimensions:	13.2" W x 31.2" D x 46.9" H

Staple Finisher-AF1/ Booklet Finisher-AF1	Tray Capacity ¹	
	Top Tray:	Up to 1,000 Sheets
	Lower Tray:	Up to 4,000 Sheets
	Paper Weight	
	Stacking:	14 lb. Bond to 150 lb. Cover (52 gsm to 400 gsm)
	Corner Stapling:	14 lb. Bond to 120 lb. Cover (52 gsm to 325 gsm)
	Booklet-Making:	14 lb. Bond to 110 lb. Cover (52 gsm to 300 gsm)
	Staple Positions:	Corner, Double-Side
	Paper Size	
	Stapling:	7.2" x 8.3" to 11.7" x 17"
	Saddle Finisher:	8.3" x 11" to 13" x 19.2"
	Stapling Capacity ¹	
	Corner/ Double Side:	Up to 100 Sheets
	Saddle-Stitch:	Up to 25 Sheets
	V-Fold:	Up to 5 Sheets without Stitch
	Power Source:	120 – 240 V, 50/60 Hz, 8 A
	Weight	
	Staple Finisher:	287 lb.
	Booklet Finisher:	397 lb.
	Dimensions:	31.5" W x 31.2" D x 48.8" H

Long Sheet Feeding and Catch Tray-D1⁹	Stack Capacity: ¹	100 Sheets
	Paper Size:	4" x 5.83" to 13" x 30"

Long Sheet Catch Tray XL-B1⁹	Stack Capacity ¹	
	Up to 30":	Up to 300 Sheets
	Up to 51.2":	Up to 10 Sheets
	Paper Size:	4" x 5.83" to 13" x 51.2"

Puncher Unit-BS1¹²	Paper Sizes	
	2-Hole:	Legal, Letter-R, Custom Size (7.2" x 7.2" to 11.7" x 17")
	3-Hole:	11" x 17", Letter, Executive-R, Custom Size (9.5" x 7.2" to 11.7" x 17")
	Paper Weight:	14 lb. Bond to 110 lb. Cover (52 gsm to 300 gsm)
	Punch Waste Capacity:	Up to 6,000 Sheets
	Power Supply:	From the Finisher

DFD Adapter and Finisher Bridge-B1⁹	Paper Weight:	14 lb. Bond to 110 lb. Cover (52 gsm to 300 gsm)
	Supported Finishing:	Plockmatic BLM50/35 SDD BLM300C Plockmatic Multi Purpose Stacker
	Requirements:	Staple/Booklet Finisher-AF1
	Weight:	168 lb.
	Dimensions:	35.8" W x 29.3" D x 46.9" H

Booklet Trimmer-G1⁹	Margin Trimming:	Front-edge Trim
	Trim Amount:	2 mm to 28 mm
	Paper Weight:	14 lb. Bond to 110 lb. Cover (52 gsm to 300 gsm)
	Power Supply:	From the Finisher
	Weight:	392 lb.
	Dimensions:	82.5" W x 31.1" D x 41" H

Two-Knife Trimmer and Conveyor Set¹⁰	Margin Trimming:	Top and Bottom
	Trim Amount:	2 mm to 15 mm
	Paper Weight:	14 lb. Bond to 110 lb. Cover (52 gsm to 300 gsm)
	Power Supply:	120 V, 50/60 Hz, 2.5 A
	Weight:	320 lb.
	Dimensions:	21.1" W x 30.3" D x 41" H

SDD Square-Fold Booklet-Maker¹⁰	Booklet Capacity: ¹	Up to 25 Sheets
	Booklet Input Size:	5.5"x 8.27" to 9.6" x 12.6"
	Paper Weight:	16 lb. Bond to 110 lb. Cover (60 gsm to 300 gsm)
	Power Supply:	120 V, 60 Hz, 15 A
	Weight:	154 lb.
	Dimensions:	43.3" W x 23.6" D x 44.9" H

Finishing Accessories (Continued):

SDD Square-Fold Booklet-Maker with Two-Knife Trim ¹⁰	Booklet Capacity: ¹	Up to 25 Sheets
	Booklet Input Size:	5.5" x 8.27" to 9.6" x 12.6"
	Booklet Output Size:	4.7" x 7.9" to 9.6" x 12.6"
	Paper Weight:	16 lb. Bond to 110 lb. Cover (60 gsm to 300 gsm)
	Trim Amount:	2 mm to 35 mm
	Power Supply:	120 V, 60 Hz, 15 A
Plockmatic BLM50/35 Professional Booklet-Maker ⁸	Weight:	573 lb.
	Dimensions:	62.7" W x 27.6" D x 51.2" H
	Booklet Size: ¹	Up to 35/50 Sheets
	Paper Size:	8.1" x 10.8" to 12.6" x 18"
	Paper Weight	
	Uncoated:	16 lb. Bond to 110 lb. Cover (60 gsm to 300 gsm)
	Coated:	28 lb. Bond to 110 lb. Cover (105 gsm to 300 gsm)
	Trim Amount	
	Face: ¹¹	1 mm to 25 mm
	Top/Bottom: ¹²	5 mm to 30 mm
	Paper Rotating: ¹²	8.1" x 10.9" to 9.1" x 12.7"
	Weight:	1,049 lb.
	Dimensions:	114.3" W x 33.8" D x 42.5" H

Print Servers

PRISMAsync Print Server ⁷	System Software:	Version 8
	CPU:	Intel® Core i7 4770S @ 3.1 GHz
	Memory:	16 GB
	Hard Drive:	1.5 TB
	OS:	Windows® 10
	Standard:	Scheduler, DocBox, G7 Calibration, Page Programmer, Remote Manager, PRISMAlytics Dashboard, Automated Workflows, Multiple Queues, Remote Control
imagePRESS Server D3000	Optional:	Advanced Imposition, DP Link
	Fiery System:	FS500 Pro
	CPU:	Intel® Core i5-6500 3.2GHz up to 3.6GHz with Turbo
	Memory:	8 GB
	Hard Drive:	2 TB
	OS:	Windows® 10
	Standard:	Fiery® Hot Folders, Virtual Printers, Unity Display, Fiery JDF, Fiery Command WorkStation 6, Paper Catalog, Fiery Spot-On, Fiery Remote Scan, Media Librarian
	Optional:	Graphic Arts Pro Package, Fiery JobMaster, Color Profiler Suite, Fiery JobFlow, Operator Attention Light, Removable HDD, Integrated Interface, and Stand-NX GL

¹ Based on 20 lb. Bond.

² Envelope Attachment Kit required.

³ POD Deck Lite-XL or Long Sheet Feed and Catch Tray-B1 required.

⁴ Multi Drawer Paper Deck-E1 or POD Deck Lite-C1 required.

⁵ Staple/Booklet Finisher-AF1 or High Capacity Stacker-J1 required.

⁶ High Capacity Stacker-J1 required.

⁷ Multi Function Professional Puncher-C1 required.

⁸ High Capacity Stacker-J1 or DFD Adapter and Finisher Bridge-B1 required.

⁹ Staple/Booklet Finisher-AF1 required.

¹⁰ Booklet Trimmer-K1 required.

¹¹ Optional trimmer required.

¹² Optional rotator required.

Canon

usa.canon.com



As an ENERGY STAR® Partner, Canon U.S.A., Inc. qualified this model as meeting the ENERGY STAR® energy efficiency criteria through an EPA recognized certification body. ENERGY STAR and the ENERGY STAR mark are registered U.S. marks. Canon and imagePRESS are registered trademarks of Canon Inc. in the United States and may also be registered trademarks or trademarks in other countries. PRISMA is a registered trademark of Canon Production Printing Netherlands B.V. All other referenced product names and marks are trademarks of their respective owners. Some printer output images may be simulated. Specifications and availability subject to change without notice. Not responsible for typographical errors.

Federal Law prohibits copying of certain documents. Violators may be subject to penalties. We suggest that you check with your own legal counsel. Canon U.S.A., Inc. and Canon Canada, Inc. intend to cooperate with Law Enforcement Agencies in connection with claims on unauthorized copying.

©2022 Canon U.S.A., Inc. All rights reserved.

0622R2-iPV1000SS-PDF-IH

