

# Canon

CANON SOLUTIONS AMERICA



imageFORMULA  
DR-6010C



 **imageFORMULA**  
**DR-6010C**

### **Fast Office Document Scanning**

The imageFORMULA DR-6010C office scanner delivers high-speed, reliable document handling and high-quality images in a small package. Flexibility, rich features, and ease of use help maximize return on investment at all levels of the business system.

### **Speed to Suit User Needs**

Employees in paper-intensive environments find themselves looking for standards to alleviate the document conversion process. The DR-6010C scanner employs technologies such as an advanced three-line CIS sensor and onboard file compression. These enable prompt transition of hard-copy documents into electronic files at fast speeds, up to 60 pages/120 images per minute in color, grayscale, and black and white.\* The DR-6010C scanner helps users save time and keeps them on pace with laborious business workflows.

### **Flexible Capabilities for Seamless Document Handling**

Users with pressing document capture needs not only require fast scanning speeds to lessen their workloads, but they must also reduce preparation time and increase unattended batch scanning time. The DR-6010C scanner exercises a diverse set of features to achieve these goals. With capabilities such as Ultrasonic Double-Feed Detection, straight paper path, and Long Document Mode, the DR-6010C scanner can reliably accommodate a wide variety of documents, including plastic cards, fragile or thick documents, and documents up to 118" in length. The DR-6010C scanner is a flexible solution for users with varied batch scanning needs.

## Dedicated Features for Detailed Image Capture

Canon realizes that within business workflows, users are not able to sacrifice scanning quantity for quality. The DR-6010C scanner concentrates advanced image processing features into a convenient design for precise yet rapid document capture. Scanning at resolutions up to 600 dpi, this device uses image processing features such as Prevent Bleed-Through and Moiré Reduction as well as sensor Shading Mechanisms to maintain the integrity of scanned documents, without forfeiting scanning speed.

## User-Friendly Solutions for Capturing and Distributing Documents

Easy integration and user-friendly features are important when deploying scanning solutions into existing corporate workflows. To help increase productivity, the DR-6010C scanner yields many user-intuitive features. Scan-To-Job buttons distribute documents directly to e-mail, printer, and other standard destinations, with one-touch access to customizable or preprogrammable scan tasks. The DR-6010C scanner is bundled with Canon CapturePerfect and Kofax VirtualReScan document imaging software for capturing and distributing newly created electronic files. This provides the first step in the Enterprise Content Management process.



## Environment in Mind

The DR-6010C scanner has been designed with Canon's initiative to take an environmental approach to product design and life cycle. For example, the scanner can be synchronized to automatically turn on and off, according to the status of the connected PC, and features a Standby Mode to help conserve power. This scanner also meets the ENERGY STAR® guidelines for energy efficiency and complies with the EU RoHS and WEEE directives for reduction of hazardous substances and waste products.



\* Examples based on typical settings, rated in pages/images per minute with letter-sized documents at 200 dpi portrait-feeding directions. Actual processing speeds may vary based on PC performance and application.

## Specifications

|                         |                                                                                                              |
|-------------------------|--------------------------------------------------------------------------------------------------------------|
| Type:                   | Departmental Scanner                                                                                         |
| Document Feeding:       | Automatic or Manual                                                                                          |
| Document Size           |                                                                                                              |
| Width:                  | 2.1" - 8.6"                                                                                                  |
| Length:                 | 2.8" - 14"                                                                                                   |
| Long Doc. Mode:         | Up to 118"                                                                                                   |
| Document Weight         |                                                                                                              |
| U-Turn Path             |                                                                                                              |
| Automatic Feeding:      | 14 - 32 lb. Bond                                                                                             |
| Manual Feeding:         | 11 - 144 lb. Bond                                                                                            |
| Straight Path           |                                                                                                              |
| Automatic Feeding:      | 14 - 32 lb. Bond                                                                                             |
| Manual Feeding:         | 11 - 40 lb. Bond                                                                                             |
| Feeder Capacity:        | 100 Sheets                                                                                                   |
| Grayscale:              | 8-bit                                                                                                        |
| Color:                  | 24-bit                                                                                                       |
| Scanning Element:       | Three-Line Contact Image Sensor (CMOS)                                                                       |
| Light Source:           | RGB LED                                                                                                      |
| Scanning Modes:         | Simplex, Duplex, Color, Grayscale, Black and White, Error Diffusion, Advanced Text Enhancement (Three Types) |
| Color Dropout:          | RGB and Custom                                                                                               |
| Optical Resolution:     | 600 dpi                                                                                                      |
| Output Resolution:      | 100/150/200/240/300/400/600 dpi                                                                              |
| Scanning Speeds*        | Simplex Duplex                                                                                               |
| Black and White:        | 60 ppm 120 ipm                                                                                               |
| Grayscale:              | 60 ppm 120 ipm                                                                                               |
| Color:                  | 60 ppm 120 ipm                                                                                               |
| Interface:              | Hi-Speed USB 2.0/SCSI-III                                                                                    |
| Scanner Drivers:        | ISIS/TWAIN for Windows * 2000/XP/Windows Vista *                                                             |
| Dimensions (H x W x D): | 7.3" x 12.5" x 10.9"                                                                                         |
| Weight:                 | 14.3 lb.                                                                                                     |
| Power Consumption:      | 33W or Less (Energy Saving Mode: 3W or Less)                                                                 |
| Suggested Daily Volume: | 7,500 Scans**                                                                                                |

### BUNDLED SOFTWARE

- ISIS/TWAIN Drivers
- Canon CapturePerfect
- Kofax VirtualReScan

### OPTIONS

- Flatbed Scanner Unit 101/201
- Exchange Roller Kit
- Barcode Module III
- eCarePAK Exchange Service

### OTHER FEATURES

- Auto Color Detection
- Auto Page Size Detection
- Batch Separation
- Custom Color Dropout/Enhance Color
- Deskew
- Folio
- Moiré Reduction
- MultiStream™
- Pre-Scan
- Prevent Bleed-Through/Remove Background
- Punch Hole Removal
- Rapid Recovery System
- Skip Blank Page
- Text Orientation Recognition
- Ultrasonic Double-Feed Detection
- User Registration

### ITEM NUMBER

3801B002

\* Examples based on typical settings, rated in pages/images per minute with letter-sized documents, portrait feeding direction, up to 200 dpi. Actual processing speeds may vary based on PC performance and application software.

\*\* Calculations based on scanning speed and assumed daily time of use.

## Utilize the imageFORMULA DR-C225 to its full potential with professional services from Canon Solutions America

When selecting and implementing new technology, a highly skilled technical team is the difference-maker for a successful deployment. Canon Solutions America has the team of experts you need to help you acquire the right technology, solutions, and services for your organization. Our team of technical professionals draws upon decades of technical expertise and real-world experience to ensure you obtain the maximum benefit from your technology investment.

As an ENERGY STAR® Partner, Canon U.S.A., Inc. has determined that this product meets the ENERGY STAR guidelines for energy efficiency. ENERGY STAR and the ENERGY STAR mark are registered U.S. marks. IMAGEFORMULA is a registered trademark of Canon Electronics Inc. CANON and CAPTUREPERFECT are registered trademarks of Canon Inc. in the United States and may also be registered trademarks or trademarks in other countries. All other referenced product names and marks are trademarks of their respective owners. Specifications and availability subject to change without notice. ©2013 Canon U.S.A., Inc. All rights reserved.



CANON SOLUTIONS AMERICA

### Canon Solutions America, Inc.

One Canon Park  
Melville, NY 11747

1.800.815.4000  
csa.canon.com

