

LEXMARKTM

E322

The Fast, Affordable Desktop Monochrome Laser Printer of Choice for Your Office

- Fast 16 ppm print speed for on-demand convenience and efficiency to keep pace with the speed of business
- Impressive 1200 image quality for professional results
- Reliable, dependable operation with high-capacity cartridges and a robust duty cycle
- Optimal processing power for printing complex documents
- Multiple data stream support for broad platform connectivity



Product Information

Part Numbers

- United States
 - E322: 08A0200
 - E322n: 08A0300

Technology

- Monochrome laser

Speed

- Up to 16 pages per minute
- Less than 12 seconds time to first page

Print Quality

- 1200 image quality
- 600 x 600 dpi
- 300 x 300 dpi with PQET

Processor

- 133 MHz RISC

Memory (std/max)

- 8MB/72MB (E322)
- 16MB/80MB (E322n)

Connectivity

- Standard
 - USB port
 - Bidirectional parallel port (E322)
 - 10BaseT/100BaseTX Ethernet (E322n)
- Optional
 - MarkNet™ X2000 series of external print servers

Compatibility

- PostScript Level 2 emulation
- PCL 6 emulation
- PPDS Migration Tool

Font Selection

- PostScript emulation
 - 75 scalable fonts
- PCL emulation
 - 75 scalable fonts
 - 2 bitmapped fonts
- PPDS fonts
 - 39 scalable fonts
 - 5 bitmapped fonts

Paper Handling

- Input
 - Standard: 150 sheets + 1 single sheet manual feed
 - Maximum: 400 sheets + 1 single sheet manual feed
 - Sources (std/max): 2/3
- Output
 - 100 + 1 single sheet straight-through path
 - Destinations (std/max): 2/2

Media

- Media sizes:
 - letter, legal, A4, A5, JIS B5 and executive
- Media types:
 - Plain paper, envelopes, card stock, paper labels and transparencies
- Media weights:
 - Plain paper: 16 to 43 lb. (60 to 163 g/m²)
 - Card stock: up to 90 lb. index (163 g/m²)

Paper Handling Options

- 250-sheet Drawer

Supplies*

The Lexmark E322 ships with:

- 3,000-page Prebate™ Print Cartridge

Other supplies:

- 3,000-page Prebate Print Cartridge
- 3,000-page Print Cartridge
- 6,000-page High Yield Prebate Print Cartridge
- 6,000-page High Yield Print Cartridge

Operating Systems

- Microsoft Windows 2000, Me, 98, 95, NT 4.0 and XP; Linux, UNIX, Novell and Mac OS
- For a complete list, see www.lexmark.com

Size/Weight

- 15.0" x 14.2" x 8.7" (W x D x H)
(380 mm x 362 mm x 221 mm)
- 19.8 lb. (9 kg)

Acoustics

- 49 dBA printing
- 35 dBA idle

Duty Cycle

- Up to 15,000 pages per month

Warranty

- 1-year LexExpressSM limited warranty
- For more warranty information, visit Warranties and Returns at www.lexmark.com

*Yield is based on approximately 5% print coverage



Competitive Comparison

	Lexmark E322/E322n	Brother HL-1450/1470N	HP 1200/1200n	HP 2200d/2200dtn
MSRP¹				
Base	\$489	\$499.99	\$499	\$999
Network	\$729	\$699.99	\$739	\$1,789
Technology	Laser	Laser	Laser	Laser
Speed	16 ppm	15 ppm	15 ppm	19 ppm
Time to First Page	< 12 seconds	< 15 seconds	< 10 seconds	< 15 seconds
Processor	133 MHz RISC	66 MHz	90 MHz	133 MHz
Max. Resolution	1200 IQ/600x600 dpi	1200x600 dpi	1200x1200 dpi	1200x1200 dpi
Memory (std./max)				
Base	8MB/72MB	8MB/36MB	8MB/72MB	8MB/72MB
Network	16MB/80MB	8MB/36MB	16MB/72MB	DN: 8MB/72MB DTN: 16MB/48MB
Flash Memory	Optional	N/A	N/A	N/A
Standard Interface				
Base	Parallel, USB	Parallel, USB	Parallel, USB	Parallel, USB, infrared port; 1 open EIO slot on D, DT
Network	USB, On-board ethernet	Parallel, USB, Ethernet	Parallel, USB, Ethernet	Parallel, USB, infrared port, Ethernet
Paper Handling				
Std. Sheets (in/out)	151/101	251/151	260/126	350/151**
Max Sheets (in/out)	401/101	501/151	260/126	850/151
Std. Sources (in/out)	2/2	2/2	2/2	2/2
Max. Sources (in/out)	3/2	3/2	2/2	3/2
Optional Input	250	250	none	250, 500
Max. Paper Size	8.5 in. x 14 in.	8.5 in x 14 in.	8.5 in. x 14 in.	8.5 in x 14 in.
Media Weight	16-43 lb. (60-163 g/m ²); card stock up to 90 lb. index (up to 163 g/m ²)	Manual: 17-43 lb. (64-163 g/m ²) Trays: 17-28 lb. (64-105 g/m ²)	Out bin: 16-28 lb. (60-105 g/m ²) Out slot: 16-43 lb. (60-163 g/m ²)	Tray 1: 16-43 lb. (60-163 g/m ²) Tray 2,3: 16-28 lb. (60-105 g/m ²)
Compatibility	PCL 5e, PCL 6, PS 2, PPDS	PCL 6, PS 2	PCL 5e, PCL 6, PS 2 emulation	PCL 5e, PCL 6, PS 2 emulation
Supply Yield (pages)* (std.) (high yield)	3,000*** 6,000	3,000 6,000	2,500 3,500	5,000
Monthly Duty Cycle	15,000 pages	10,000 pages	10,000 pages	40,000 pages
Warranty	1-year LexExpress	1-year Express Exchange	1-year	1-year Express Exchange

¹ Manufacturer's Suggested Retail Price

*Yield at approximately 5% coverage

**DTN model includes 500-sheet output

***Ships with E322 and E322n models



LEXMARKTM E322

The monochrome laser printer of
choice for your office



Order Information Chart

Part Number	UPC	Description
United States		
08A0200	7-34646-51200-8	Lexmark E322
08A0300	7-34646-51300-5	Lexmark E322n
SUPPLIES		
Print Cartridges*		
08A0475	7-34646-36872-8	3,000-page Print Cartridge
08A0476	7-34646-36873-5	3,000-page <i>Prebate</i> Print Cartridge
08A0477	7-34646-36874-2	6,000-page High Yield Print Cartridge
08A0478	7-34646-36875-9	6,000-page High Yield <i>Prebate</i> Print Cartridge
Media		
70X7240	7-34646-03810-2	Transparencies (letter)
OPTIONS AND FEATURES		
Paper Handling		
08A0480	7-34646-36877-3	250-sheet Drawer
08A0481	7-34646-36878-0	250-sheet Tray
12A2435	7-34646-18435-9	Paper Tray Cover
08A0461	7-34646-37176-6	Paper Tray 2 Cover
SDRAM Memory DIMMs		
5K00013	7-34646-28612-1	4MB SDRAM
5K00014	7-34646-28613-8	8MB SDRAM
5K00015	7-34646-28614-5	16MB SDRAM
5K00016	7-34646-28615-2	32MB SDRAM
5K00017	7-34646-28616-9	64MB SDRAM
Flash SIMMs		
45H0021	7-34646-12640-3	2MB Flash SIMM
45H0022	7-34646-12641-0	4MB Flash SIMM
APPLICATION SOLUTIONS		
Optra Forms		
11N0056	7-34646-30810-6	Optra Forms Manager CD
11N0040	7-34646-20731-7	Optra Forms 4.3c Software
11H0052	7-34646-20732-4	Optra Forms Director
43H5065	7-34646-13753-9	Optra Forms 2MB Flash SIMM
43H5066	7-34646-13754-6	Optra Forms 4MB Flash SIMM
CONNECTIVITY		
External Print Servers		
46D0060	7-34646-30316-3	MarkNet X2011e Ethernet 10/100BaseTX – 1-Port
46D0040	7-34646-30315-6	MarkNet X2012e Ethernet 10/100BaseTX/10Base2 – 1-Port
46D0020	7-34646-30314-9	MarkNet X2031e Ethernet 10/100BaseTX – 3-Port
46D0000	7-34646-30313-2	MarkNet X2030t Token-Ring – 3-Port
Cables and Attachment Options		
1368705	7-34646-11309-0	External Serial Adapter
1329605	0-87944-09056-4	Parallel (10') Cable
1427498	7-34646-13068-4	Parallel (20') Cable
12A2405	7-34646-18340-6	USB (2-Meter) Cable
1038693	7-34646-21649-4	Serial (50') Cable

*Yield at approximately 5% coverage

Printed on a Lexmark C910.

Lexmark International, Inc. is a global developer, manufacturer and supplier of printing solutions and products, including laser, inkjet and dot matrix printers and associated consumable supplies for the office and home markets. Lexmark is on the internet at www.lexmark.com. Prices and other information subject to change without notice. Lexmark, Lexmark with diamond design and MarkNet are trademarks of Lexmark International, Inc., registered in the United States and/or other countries. LexExpress is a service mark of Lexmark International, Inc. LocalTalk, Mac OS and Mac Logo are trademarks of Apple Computer, Inc., registered in the United States and/or other countries. PCL is a trademark of Hewlett-Packard Company. All other trademarks are the properties of their respective owners. As an ENERGY STAR Partner, Lexmark International, Inc. has determined that this product meets the ENERGY STAR guidelines for energy efficiency. ENERGY STAR is a US registered trademark.



LEXMARKTM
Passion for printing ideas.TM

©2001 Lexmark International, Inc.
All Rights Reserved
10/29/2001