

Lexmark E330 Laser Printer



Flexible



Up to 27 ppm printing

Up to 1200 x 1200 dpi print resolution

PostScript 3 and PCL 6 emulations; PPDS Migration Tool

USB and parallel ports standard

PC and Mac compatible in a broad range of environments

LEXMARKTM

Lexmark



Lexmark E330



Lexmark E330 with optional
550-sheet drawer

E330

Superior Performance

Up to 27 ppm printing.

< 8 seconds time to first page.

200 MHz processor with 32MB memory.

Flexibility

550-sheet optional drawer for additional paper capacity.

Networking options available.

Memory expansion available.

Parallel and USB standard.

Robust monthly volume of up to 15,000 pages.

Ease of Use

Two-piece toner cartridge and photoconductor imaging system is clean and easy to install or replace.

Photoconductor kit lasts up to 30,000 pages.

6,000-page toner cartridge keeps your office productive and efficient with less ordering and fewer replacements.

Excellent Print Quality

Adjustable print resolution settings let you optimize print quality and performance.

High-quality results on various media weights and types.

A high-performance desktop laser printer with reliable input that is ideal for the growing needs of your business.

	Lexmark E330
Part Number	US/Canada: 22S0500
Technology	Monochrome laser
Speed	Up to 27 ppm
Resolution	1200 x 1200 dpi, 2400 image quality, 1200 image quality, 600 x 600 dpi
Time to First Page	< 8 seconds
Processor	200 MHz
Memory (std./max.)	32MB/160MB
Connectivity	Standard: Bidirectional parallel port and USB port Optional: MarkNet X2000 series of external print servers supported through the parallel port; N4000e Ethernet print server supported through the USB port; External serial adapter
Operating Systems	Microsoft Windows 98SE, Me, 2000, NT 4.0, XP and Server 2003; Linux; UNIX; Novell; Mac OS For a complete list, visit www.lexmark.com
Emulations	PS 3 and PCL 6 emulations; PPDS Migration Tool
Fonts	PostScript 3 emulation: 89 scalable PCL 6 emulation: 84 + 5 scalable, including OCR-A, OCR-B and 3 of 9 barcode. Bitmapped: 2. PPDS Migration Tool: 39 scalable. Bitmapped: 5.
Paper Capacity (sheets)	
Input: Standard	250 + 1
Maximum	250 + 550 + 1
Output: Standard	250 + 1
Maximum	250 + 1
Paper Options	250-sheet tray, 550-sheet drawer, 550-sheet tray
Paper Sources	
Input: Standard	2
Maximum	3
Output: Standard	2
Maximum	2
Media Types	Plain paper, card stock, envelopes, transparencies and paper labels
Media Sizes	Letter, legal, A4, A5, B5, executive, universal, statement and folio
Media Weights	Plain paper: 16-24 lb. (60-90 g/m ²) Card stock: up to 90 lb. index (163 g/m ²)
Size/Weight	15.6" x 13.9" x 9.8" (W x D x H) (396.2 mm x 353.1 mm x 248.9 mm)/22 lb. (9.98 kg)
Acoustics	52 dBA printing; 30 dBA idle
Supplies¹	Ships with: 1,500-page Starter Return Program Toner Cartridge and up to 30,000-page Photoconductor Kit Supplies: 6,000-page Return Program Toner Cartridge 6,000-page Toner Cartridge 2,500-page Return Program Toner Cartridge 2,500-page Toner Cartridge Up to 30,000-page Photoconductor Kit
Duty Cycle	Up to 15,000 pages per month
Warranty	1-year LexExpress SM

¹ Yield is based on approximately 5% print coverage

Order Information Chart

Part No.	UPC	Description
US/Canada		
22S0500	7-34646-01700-8	Lexmark E330
SUPPLIES		
Print Cartridges		
12A8405	7-34646-38630-2	6,000-page Return Program Toner Cartridge
12A8305	7-34646-38628-9	6,000-page Toner Cartridge
12A8400	7-34646-38629-6	2,500-page Return Program Toner Cartridge
12A8300	7-34646-38626-5	2,500-page Toner Cartridge
Other Supplies		
12A8302	7-34646-38627-2	Photoconductor Kit
Media		
70X7240	7-34646-03810-2	Transparencies (Letter, 50 sheets)
12A5010	7-34646-13899-4	Transparencies (A4, 50 sheets)
OPTIONS AND FEATURES		
Paper Handling Options		
22S0300	7-34646-02415-0	250-Sheet Tray
22S0302	7-34646-02417-4	550-Sheet Drawer with Tray
22S0301	7-34646-02416-7	550-Sheet Tray
Memory Options		
16H0056	7-34646-24756-6	16MB SDRAM
16H0057	7-34646-24757-3	32MB SDRAM
16H0058	7-34646-24758-0	64MB SDRAM
16H0059	7-34646-24759-7	128MB SDRAM
Flash Memory Options		
11K4616	7-34646-12127-9	16MB Flash Card
11K4632	7-34646-12128-6	32MB Flash Card
Font Options		
10G0745	7-34646-12143-9	Traditional Chinese Font Card
10G0744	7-34646-12142-2	Simplified Chinese Font Card
10G0746	7-34646-12144-6	Japanese Font Card
10G0743	7-34646-12383-9	Korean Font Card

Part No.	UPC	Description
Application Solutions		
Optra Forms Solutions		
11N0040	7-34646-20731-7	Optra Forms Software
11N0052	7-34646-20732-4	Optra Forms Director
11N0056	7-34646-30810-6	Optra Forms Manager
10G0747	7-34646-12145-3	Optra Forms 16MB Flash Card
10G0748	7-34646-12146-0	Optra Forms 32MB Flash Card
Network Connections		
External Print Servers		
46D0060	7-34646-30316-3	MarkNet X2011e Ethernet 10/100BaseTX – 1-port
46D0040	7-34646-30315-6	MarkNet X2012e Ethernet 10/100BaseTX, 10Base2 – 1-port
46D0020	7-34646-30314-9	MarkNet X2031e Ethernet 10/100BaseTX – 3-port
46D0000	7-34646-30313-2	MarkNet X2030t Token-Ring – 4/16 3-port
14T0030	7-34646-02509-6	N4000e Ethernet Print Server 10/100BaseTX – 1-port
OTHER ATTACHMENT OPTIONS		
Adapters		
1368705	7-34646-11309-0	External Serial Adapter
Cables		
1329605	0-87944-09056-4	Parallel Cable (10 ft.)
1038693	7-34646-21649-4	Serial Cable (50 ft.)
12A2405	7-34646-18340-6	USB Cable (2-meter)



LEXMARKTM

Lexmark, Lexmark with diamond design, LexExpress and MarkNet are trademarks of Lexmark International, Inc., registered in the United States and/or other countries. Optra Forms is a trademark of Lexmark International, Inc. PostScript is a registered trademark of Adobe Systems Incorporated. ENERGY STAR is a registered U.S. mark. PCL is a registered trademark of Hewlett-Packard Company. Mac and the Mac logo are trademarks of Apple Computer, Inc., registered in the United States and/or other countries. The USB-IF logos are trademarks of Universal Serial Bus Implementers Forum, Inc. All other trademarks are the property of their respective owners.