

Professional Address Label Printer with Wireless



A professional wired & wireless network label printer.

Brother's QL-720NW offers IT managers a professional, networked label printing solution for a busy office. With wired and wireless networking connections built-in, and the option to create and print labels directly from your iOS or Android device with Brother's free iPrint & Label app, it can be shared widely by everyone in your organisation.

Although compact and easy to use, it's packed full of features to help you produce professional, customised labels. Such as fast print speeds of 93 labels per minute, high print quality of 300 x 600 dpi, easy to change rolls and a suite of free software included to help you integrate with Microsoft Word, Excel, Outlook and your corporate network.

Key Features

- Save time up to 93 labels per minute print speed
- Durable Automatic cutter
- Share amongst users with wireless and Network connectivity.
- Versatile – Choose from a range of pre-sized and continuous labels for different applications
- print address labels directly from Microsoft Word, Excel and Outlook
- Space-saving – compact size

Supplies

Die Cut labels

Standard address label (400)	29 x 90mm	DK-11201
Large address label (400)	38 x 90mm	DK-11208
Small address label (400)	29 x 62mm	DK-11209
Shipping label (400)	62 x 100mm	DK-11202
File folder label(400)	17 x 87mm	DK-11203
Multi-purpose label (400)	17 x 54mm	DK-11204
Square label (400)	23 x 23mm	DK-11221
CD/DVD label (400)	58mm	DK-11207
Round Label (400)	12mm	DK-11219
Round Label (400)	24mm	DK-11218

Continuous-length labels (30.48 meters)

12mm	DK22214	29mm	DK22210
38mm	DK22225	50mm	DK22223
62mm	DK22205		
54mm	Non Adhesive		DKN55224
62mm	Removable (White)		DK44205
62mm	Removable (Yellow)		DK44605

Continuous-length labels (film 15.24 meters)

29mm	DK22211	62mm white	DK22212
62mm Yellow	DK22606	62mm clear	DK22113

Optional Extras

- None available

Product Specifications

Housing Colour	Black and White
Key Board	No
Number of Keys	4 (On/Off, Editor Lite, Feed, Cut)
Cutter	Durable Auto cutter (User irreplaceable)
Auto Half Cutter	No
Power	Internal S/W Power Supply
LCD	No
LED	2 (STATUS: 3 colour - Green, Red, Orange / Editor Lite: 1 colour - Green)
Print Method	Thermal
Print Head	300 dpi / 720 dots
Print Speed	150 mm (5.9") / sec / 93 standard address labels / min.
Roll Type	DK rolls (DK Die-cut Labels / DK Continuous Length Tape)
Roll Width	Max. Label width 62mm (2.4")
Max. Print Width	59mm (2.3") max.
Printable Label Length	12.7mm (0.5") - 1m (3')
Printer Driver	QL-710W
Computer Interface	USB(Full Speed), RS-232C, 10/100 BASE-TX Wired LAN, IEEE802.11b/g/n Wireless LAN,
Network Protocol	Protocol (IPv4) ARP, RARP, BOOTP, DHCP, APIPA (Auto IP), WINS/NetBIOS name resolution, DNS Resolver, mDNS, LLNMR responder, LPR/LPD, Custom Raw Port/Port9100, FTP, Server, TFTP server, SNMPv1/v2c, ICMP
Wireless Security	Wireless SSID (32 chr), WEP 64/128 bit, WPA-PSK (TKIP/AES), WPA2-PSK (AES), LEAP, EAP-FA
Label Editing Software	Win: P-touch Editor ver. 5.0, P-touch Address Book ver. 1.1 Mac: P-touch Editor ver. 5.0
Bar Code	Software side: CODE39, CODE128, UCC/EAN128(GS1-128), ITF(I-2/5), CODABAR(NW-7), UPC-A, UPC-E, EAN13, EAN8, ISBN-2(EAN13 AddOn2), ISBN-5(EAN13 AddOn5), Laser Barcode, POSTNET, RSS(RSS14 Standard, RSS14 Truncated, RSS14 Stacked, RSS14 Stacked Omni, RSS Limited, RSS Expanded, RSS Expanded Stacked), PDF417(Standard, Truncate, Micro), QR code(Model1, Model2, Micro), Data Matrix(ECC Square, ECC Rectangular), MaxiCode(Model2, Model3, Model4, Model5)
Add-in for Microsoft	Win: Word, Outlook, Excel
Database file compatibility	Win: csv, txt, mdb, xls Mac: csv, txt

Weights/ Dimensions/ Measures

Dimensions

128mm(W) x 236mm(D) x 153mm(H)

Weight

1.2kg (without DK roll)

What's in the box

CD-ROM (P-touch Editor 5.0 for Windows, P-touch Address Book 1.1, P-touch Editor 5.0 for Mac, Printer Driver, User's Guide, Software User's Guide)
Quick Setup Guide, DK Rolls Line-up Guide
USB cable, Warranty card
DK-11201 Standard Address Labels (100 labels)
DK-22205 (62mm Continuous) Starter roll (8 m)
Registration Insertion, AC Power cord, EEE insertion

