



imageRUNNER™
2010F




Digital Multifunction Workgroup Solution

Introducing the imageRUNNER™ 2010F from Canon—delivering exceptional digital multifunction and document management capabilities for the needs of small- to mid-size workgroups and businesses.

The imageRUNNER 2010F will optimize productivity and efficiency by providing benchmark performance, exceptional value, and accessories that enable customers to select the most appropriate solution for their needs.

In one space-saving product, the imageRUNNER 2010F delivers digital copying, faxing features, optional network printing, and sending capabilities, as well as the highest levels of image quality, network integration, and elevated multitasking capabilities on the market. This allows your organization to manage its hard-copy and electronic-based information, regardless of form, content, or location, giving you the levels of efficiency you're accustomed to, plus a competitive advantage.





imageRUNNER™
2010F

imageRUNNER 2010F Specifications

Main Unit

Type:	Digital, Multifunction Imaging System
Copying System:	Laser Dry Electrostatic Transfer
Developing System:	Dry Monocomponent Toner Projection
Fixing System:	Heat Roller Fusing
Image Server:	Standard 16MB (Approx. 120 Pages) Up to 80MB Max.
First-copy Time:	8.3 Seconds (Platen Glass, Letter, Direct, Paper Drawer 1)
Warm-up Time:	30 Seconds or Less (Main Power Switch On) 10 Seconds or Less (Operation Panel Switch On)
Output Speed:	20 ppm (Letter)
Max. Copy Reservation:	No limit (Up to Memory Capacity)
Scanning Resolution:	600 dpi x 600 dpi
Engine Resolution:	600 dpi x 600 dpi
Interpolated Resolution:	1200 dpi x 600 dpi (Copy) 2400 dpi x 600 dpi (Print)
Halftone:	256 Gradations of Gray
Duplexing:	Not Supported
Magnification:	50% to 200% (in 1% Increments)
Preset Reduction:	50%, 64%, 73%, 78%
Preset Enlargement:	121%, 129%, 200%
Paper Supply	
Standard:	2 x 250-sheet Paper Cassette 100-sheet Stack Bypass
Optional:	2 x 250-sheet Paper Cassette
Exposure Control:	Automatic or Manual
Multiple Copies:	1 to 99
Max. Original Size:	11"x 17" (Ledger)
Acceptable Paper Weights	
Paper Drawer:	17 lb. to 24 lb. Bond (64 - 90 g/m ²)
Stack Bypass:	17 lb. to 32 lb. Index (64 - 128 g/m ²)
Power Source:	120V, 60Hz, 10A
Drum:	OPC—Estimated Yield: 21,000 Impressions
Max. Duty Cycle:	50,000 Impressions Per Month
Toner:	Estimated Yield: 7,850 Images (at 6% Coverage)
Dimensions (H x W x D):	29-1/2" x 24-1/4" x 24-7/8" (747mm x 615mm x 631mm) Approx. 111 lb. (50.5kg)
Weight:	
Super G3 Fax (Standard)	
Applicable Line:	Public Switched Telephone Network (PSTN)
Connection Lines:	1 (2 option)
Transmission Time:*	ECM-MMR Approx. 3 Seconds per Page (33,600 bps)
Compression System:	MH, MR, MMR, JBIG
Sending Sizes:	Statement to Ledger
Auto-dial Function:	One-touch Speed-dialing: 63 Coded Speed-dialing: 137
Image Memory:	2MB Standard (Shared from Main Unit, up to 100 Pages)

Send Feature (Optional)

Sending Methods:	E-Mail, I-Fax, Super G3 Fax File Server (FTP)
Number of Addresses:	200
File Format:	M-TIFF (MH/MR/MMR), PDF
Sending Resolution:	200 dpi x 100 dpi, 200 dpi x 200 dpi, 300 dpi x 300 dpi, 200 dpi x 400 dpi 400 dpi x 400 dpi

Accessories

ADF-J1 (Standard)

Acceptable Original Size:	Statement to Ledger 50 Sheets (20 lb./Statement, Letter)
Paper Capacity:	25 Sheets (20 lb./Ledger, Legal)
Acceptable Paper Weight:	14 lb. to 28 lb. Bond

Finisher-L1 (Optional)

Acceptable Paper Weight:	17 lb. to 32 lb. Bond
Number of Trays:	One
Tray Capacity:	Non-collate/Collate Mode - 300 Sheets (Letter) Staple Mode - 30 Sets (Letter)
Staple Position/Capacity:	Top Corner/15 Sheets

Inner 2-Way Tray (Optional)

Number of Trays:	Two (with Main Tray)
Capacity Per Tray:	Top Tray: 100 Sheets (Letter) Main Tray: 250 Sheets (Letter)
Paper Size:	Statement to Ledger

Cassette Feeding Module-G1 (Optional)

Paper Capacity:	2 x 250-sheet Paper Cassette
Paper Size:	Statement to Ledger
Acceptable Paper Weight:	17 lb. to 24 lb. Bond

Printer Board-N1 (Optional)

Type:	Embedded Print Controller
Processor:	Power PC405 200MHz RISC Processor
Memory:	Standard 8MB (72MB Max.)
Storage:	Optional 10GB HDD (Only Used for Stored Job and Secured Printing Features)
PDL Support:	PCL 5e, PCL 6, PostScript® 3™ (PS3 Only Supported with Optional PS Module-B1)
Internal Fonts:	PCL 5e/6: 80 Roman Fonts, 32 Bar-code Fonts
Interface Connections:	Parallel (IEEE1284) USB 1.1 Optional RJ-45 (10/100Base-T) (Compatibility: Nibble, Byte, and ECP mode)
Other Features:	Access to Full Finishing Features Spooling Supported

Ethernet Network Interface Adaptor IN-E5 (Optional)

CPU:	ETRAX 100LX (32-bit RISC CPU 100MHz)
Memory (RAM):	4MB
Memory (ROM):	2MB (Flash™)
SDRAM:	128 Kbytes
Network I/F:	10Base-T, 100Base-TX (RJ-45)
Network OS:	Novell® NetWare® v.3.2, 4.1, 4.2, 4.11, 5.0, 5.1 (IPX/SPX) Windows® 95/98/Me (TCP/IP) Windows NT 4.0/Windows 2000/ Windows XP (TCP/IP) Mac OS 7.5 or Later (DDP) Solaris™ 1.1x, 2.5 or Later (TCP/IP)
Protocol Stacks:	IPX/SPX:™ 802.2, 802.3, Ethernet II, 802.2 SNAP, Canon NDPs Gateway, TCP/IP, SMB, AppleTalk:™ 802.2 SNAP and AppleTalk Phase II only
Other Features:	Remote UI™ Supported NetSpot® Supported

Other Accessories

- PS Module-B1
- 32MB Expansion Memory for Main Unit
- 64MB Expansion Memory for Printer Board-N1
- 32MB Expansion Memory for Printer Board-N1
- 10GB Hard Disk HD-65 for Printer Board-N1
- Flash ROM Module-FR-65
- FL Cassette-W1
- Super G3 Fax Expansion Kit-B1
- Large Cabinet
- Small Cabinet
- Card Reader-E1
- Basic Card Set
- Copy Card Set 1
- Copy Card Set 2
- Copy Card Set 3

Supplies/Consumables

- Staple-K1 (for Finisher-L1)
- Transparency Type E
- Matte Labels
- Black Toner
- Drum Unit

* Approximate 3-second-per-page fax transmission time based on ITU-T No. 1 Chart (MMR, Standard Mode) at 33.6 Kbps modem speed when transmitting to another V.34 machine. The Public Switched Telephone Network (PSTN) currently supports 28.8 Kbps modem speed or lower, depending on the telephone line conditions.

As an ENERGY STAR® Partner, Canon U.S.A., Inc. has determined that this product meets the ENERGY STAR® guidelines for energy efficiency. ENERGY STAR and the ENERGY STAR certification are registered U.S. trademarks. PostScript is a registered trademark of Adobe Systems Incorporated in the United States and/or other countries. Flash is a trademark of Macromedia, Inc. Novell and NetWare are registered trademarks of Novell, Inc. in the United States and other countries. IPX/SPX is a trademark of Novell, Inc. AppleTalk is a trademark of Apple Computer, Inc., registered in the U.S. and other countries. Windows and Windows NT are registered trademarks of Microsoft Corporation in the United States and/or other countries. Solaris is a trademark of Sun Microsystems, Inc. in the U.S. and other countries. Canon and NetSpot are registered trademarks, and IMAGERUNNER, Canon Know How, and the GENUINE logo are trademarks of Canon Inc. Remote UI is a trademark, and IMAGEANYWARE is a service mark of Canon U.S.A., Inc. All other terms and product names may be trademarks or registered trademarks of their respective owners, and are hereby acknowledged.

Specifications subject to change without notice.

Canon KNOW HOW™

1-800-OK-CANON
www.usa.canon.com

Canon U.S.A., Inc.
One Canon Plaza
Lake Success, NY 11042

0033W537

0802-IR2010F-75M

