

Canon

 **imageRUNNER**
LBP3470



desktop productivity
black and white
networked
compact design

OFFICE SOLUTIONS



At-a-Glance



imageRUNNER LBP3470



Standard Duplex Printing



Up to 8.5" x 14"



Up to 600 x 600 dpi



Black and White

Robust performance

- > Up to 35-ppm printing (Letter)
- > Standard UFR II, PCL 5e/6, and PostScript 3 Emulation
- > Standard 128MB RAM
- > Standard Ethernet and USB 2.0 Hi-Speed
- > Fast warm-up time, 10 seconds or less
- > Fast first-print time, 6 seconds or less

Outstanding paper handling

- > Standard 250-sheet cassette
- > 50-sheet stack bypass tray
- > Up to 800-sheet maximum paper capacity
- > Auto-duplexing
- > Output tray full detection

Exceptional usability

- > Streamlined one-line LCD display panel
- > Dedicated job cancel button
- > Available paper cassette closing assist mechanism
- > Support for Canon imageWARE Enterprise Management Console

Crisp black-and-white output. Fast, compact, and friendly to the environment.

Compact desktop performance

The new Canon imageRUNNER LBP3470 model is the ideal choice for small corporate workgroups and small offices. Leveraging Canon's patented RAPID Fusing System, the device produces ultra-crisp monochrome documents at up to 35 ppm (LTR) with quick first-print times and automatic duplexing, despite its compact size and low energy consumption. For larger print operations, an optional paper cassette allows for up to 800 total sheets. Canon's innovative paper-level sensor proactively prevents problems by detecting when the output tray is full, and then it automatically resumes printing when the tray is emptied.

Flexible printing options

Support for UFR II, PCL5e/6, and PostScript 3 Emulation is standard on the Canon imageRUNNER LBP3470 model, giving you the flexibility to choose how to produce your documents. UFR II is optimized to produce high-speed output by automatically sharing processing tasks between the desktop computer and the printer. PostScript 3 support delivers accurate rasterization of PS3 print data, particularly useful for design, publishing, education, and healthcare businesses. Canon's print driver architecture and layout are

highly consistent for all driver types throughout the entire imageRUNNER line, simplifying output and ensuring a familiar user experience across different Canon devices.

Uncomplicated operation

Users will appreciate the streamlined interface of the Canon imageRUNNER LBP3470 model, which features a one-line LCD display. Replacing the all-in-one toner and drum cartridge is also simple through the front-access panel, and reloading paper is easy with a new closing assist mechanism.* Opening the front cover to replace toner is simplified with a single button, and print jobs can be easily cancelled with a dedicated key on the panel.

Robust administration

Managing Canon imageRUNNER devices is easy with imageWARE Enterprise Management Console. Administrators can remotely monitor the status of an entire fleet of MFPs and printers across the network to help maintain uptime for users and even push drivers to desktop computers to make deployment seamless.



* The imageRUNNER LBP3470 model offers closing assist on the optional cassette only.

Product Specifications

Main Unit

Type	Desktop Laser Printer
Printing Method	Electrophoto Method (RAPID Fusing System)
Developing System	Dry Dual Component Delivery System
Standard PDL	UFR II, PCL 5e/6, PS 3 Emulation
Power Supply	120-127V, 60Hz
Plug	NEMA 5-15P
Memory	Standard: 128MB RAM Maximum: 320MB RAM*
CPU	R4000 Series - 333MHz**
Interface Connections	10Base-T/100Base-TX
Other Interface	USB 2.0 Hi-Speed
User Interface	LCD 16 Characters x 1 Line, 8 LED Indicators, 8 Operation Keys
Print Speed (BW)	35 ppm (Letter)
Warm-Up Time	10 Seconds or Less
First-Print Time	6 Seconds or Less

Resolution	Print: UFR II/PCL 5e/6/PS 3: 600 x 600 dpi 2400-dpi Equivalent x 600 dpi
Engine:	600 x 600 dpi
Halftone:	256 Gradation (Continuous-Tone)
Print Drivers	UFR II/PS 3: Windows® 2000/XP/ Server 2003/Server 2008/ Windows Vista®/7/ Mac OS 10.4 or Later/ Linux/Citrix MetaFrame/ XenApp
PCL 5e/6:	Windows 2000/XP/ Server 2003/Server 2008/ Windows Vista/7/Linux/ Citrix MetaFrame/XenApp
Dimensions (H x W x D)	10-1/2" x 15-3/4" x 14-4/5" (267mm x 400mm x 376mm)
Installation Space (H x W x D)	15-3/4" x 23-1/5" (400mm x 589mm) (with Multi-Purpose Tray Extended)
Weight	Approx. 25.6 lb. (11.6kg)***
Power Consumption (Approx., Average)	Operating: 580W Standby: 11W Deep Sleep Mode: 5W

Paper Sources	Standard: 250-sheet Paper Cassette (20 lb. Bond) 50-sheet Multi-Purpose Tray
Optional:	500-sheet Paper Cassette
Maximum:	800 Sheets
Paper Sizes	Drawers: Legal, Letter, Executive, Custom Sizes (Width: 4" to 8-1/2" Length: 5-4/5" to 14")
Multi-Purpose Tray:	Legal, Letter, Executive, Index Card, Custom Sizes (Width: 3" to 8-1/2" Length: 5" to 14") and Envelopes
Maximum Size:	Legal (8-1/2" x 14")
Paper Weight	Cassettes: 16 lb. Bond to 32 lb. Bond (60 - 120 g/m²)
Multi-Purpose Tray:	16 lb. Bond to 43 lb. Bond (60 - 163 g/m²)
Paper Handling	Paper Output: Face-down/Face-up Output: Approx. 150 Sheets/ Capacity: 1 Sheet
Duplexing:	Standard Automatic Trayless Duplexing (Legal, Letter)
Toner	Black (Starter): 2,100 Standard Pages† Black: 6,400 Standard Pages†

Paper Feeder Unit PF-44

Paper Sizes:	Legal, Letter, Executive, Custom Sizes (Width: 4" to 8-1/2"; Length: 5-4/5" to 14")
Cassette Capacity:	500 Sheets (20 lb. Bond)
Dimensions (H x W x D)	6-1/2" x 15-3/8" x 17-2/5" (166mm x 390mm x 441mm)
Weight	Approx. 9 lb.(4.1kg)

Other Optional Accessories

- Expansion RAM ER-128
- Expansion RAM ER-256

* One memory slot available for expanding memory. Memory update requires removal of standard memory.

** The upper limit of the frequency range.

*** Excluding the CRG.

† Toner cartridge yield in accordance with ISO/IEC 19752.

Canon
*image*ANYWARE

1-800-OK-CANON
www.usa.canon.com

Canon U.S.A., Inc.
One Canon Plaza
Lake Success, NY 11042

As an ENERGY STAR® Partner, Canon U.S.A., Inc. has determined that this product meets the ENERGY STAR guidelines for energy efficiency. ENERGY STAR and the ENERGY STAR mark are registered U.S. marks. CANON, imageRUNNER, and the GENUINE logo are registered trademarks of Canon Inc. in the United States and may also be registered trademarks or trademarks in other countries. IMAGEWARE is a trademark of Canon U.S.A., Inc. in the United States and is a trademark of Canon Inc. in certain other countries. IMAGEANYWARE is a trademark of Canon. All other referenced product names and marks are trademarks of their respective owners and are hereby acknowledged. Some items may not be available at this time; please check for availability. Specifications and availability subject to change without notice.

© 2010 Canon U.S.A., Inc. All rights reserved.

0910-3470-PDF-SP

