

ECOSYS

FS-1000⁺

The clever office professional.



- ▶ 12 pages A4 per minute
- ▶ 5 emulations, optional PostScript
- ▶ 250 sheet universal cassette
+ 50 sheet multi-purpose tray
- ▶ optional 250 sheet paper feeder
- ▶ lowest cost per page in its class
- ▶ Design by F. A. Porsche

Even at first glance, it's obvious that the FS-1000⁺ is made of the right stuff. This isn't just because of its exclusive design by F. A. Porsche: as well as good looks, the FS-1000⁺ has got the talent to match. With its 250 sheet universal cassette and 50 sheet multi-purpose tray, it can easily

deal with all types of print formats. The Remote Operation Panel is also an advantage – it allows the most important print operations to be monitored and controlled from your PC. The FS-1000⁺ is one new recruit whose office career is really going places.



print ▲ copy ▲ scan ▲ fax

**The best solution.
That's what I want.**

 **KYOCERA**
mita

Specification

FS-1000⁺

ECOSYS technology is based on extremely durable components. The drum, developer and fuser of the FS-1000⁺ are designed for 100,000 pages. Due to the fact that toner is the only consumable required, ECOLaser Printers operate with the lowest costs per page in their class, and they are particularly environmentally friendly. Thanks to their numerous system, paper options and modularity, all ECOLaser Printers can develop to meet further requirements.

PRESCRIBE IIe

With the Kyocera Mita page design and control language PRESCRIBE IIe, even complex graphics, logos and standard forms can be created independently of the system and saved in the printer. Consequently, integration into print files no longer applies. They are only accessed as required and therefore relieve the load on the network.

Engine

Technology

Kyocera Mita ECOSYS, Laser

Print speed

up to 12 ppm (A4)
1st page < 13 sec.

Resolution

600 dpi, with KIR2 up to 2400 dpi

Duty cycle

max. 8.000 pages per month

Paper specification

60 – 105 g/m² normal and recycled paper,
60 – 163 g/m² OHP film, laser labels, envelopes

Paper processing

Paper feed

250 sheet universal cassette 60 – 105 g/m² A4, A5, B5, Letter, Legal, Custom (148 x 210 mm – 216 x 297 mm)
50 sheet multi-purpose tray 60 – 163 g/m² A4, A5, B5, Letter, Legal, Custom (70 x 148 mm – 216 x 297 mm)

Paper output

150 sheet face down/30 sheet face up

Controller

CPU

PowerPC 75 MHz

Memory

4 MB + ECOMemory,
max. 132 MB in 1 DIMM slots

Emulations

PCL6 incl. PjL*, Diablo 630*, IBM Proprinter X24E*,
Epson LQ-850*, Lineprinter*

Controller language

PRESCRIBE IIe

Fonts

45 scaleable fonts, incl. International character set, 45 bar codes (e.g. EAN8/EAN13/EAN128) with automatic checksum generation, incl. two dimensional bar code PDF-417
Downloadable fonts: Kyocera Mita, PCL, type 1+3

Interfaces/network

Standard interfaces

High speed bi-directional parallel (IEEE 1284, Windows95/98/2000*/ME* compliant), optional interface

Multiple Interface Connection (MIC)

MIC allows for simultaneous data transfer via up to three interfaces, with each interface having its own virtual printer.

Typefaces and bar codes

The 45 scalable, high-quality fonts can be selected from all emulations. It is therefore also possible to integrate old systems without any problems. A total of 45 integrated bar codes including hash totals are computed automatically by the printer and printed in the desired size, alignment and position.

API for individual solutions

The Application Programming Interface (API) is a highly efficient interface for the programming of individual print solutions - e.g. for the management of standard forms and documents. API is 100% compatible with applications by SAP and UNIX systems and therefore it allows the integration of popular output management systems.

Kyocera PrintMonitor (KPM)

The KPM enables complete monitoring and control of ECOLaser Printers and digital Kyocera Mita copying machines from every computer. KPM therefore offers ideal network administration as well as supporting the standardised protocol SNMP.

Remote Operation Panel

The Remote Operation Panel is a display to control all the important print operations directly from the desktop from a PC-System.

Guarantee

2 years warranty as standard. Kyocera Mita guarantees the drum and developer for 3 years or 100,000 pages (whichever occurs sooner), provided each printer is used and cleaned in accordance with the service instructions.



The up to 5 year on-site warranty extension for printer and options.

Options

Optional memory

RAM

MD-8: 8 MB; MD-32: 32 MB; MD-64: 64 MB;
MD-128: 128 MB

Optional typefaces

PK-6

35 PostScript* II Fonts (KPDL2)

OCR-2

OCR-Font ROM with OCR-A and OCR-B

Optional paper processing

Paper feeder PF-17

250 sheets 60 – 105 g/m² A4, A5, B5, Letter, Legal, Custom

Optional interfaces/network

SB-80

2. parallel interface

IB-10e

RS-232C/RS422A
serial interface (up to 115.200 Bps.)

SB-50/SB-60/SB-110/SB-110FX/SB-140

Fiberlink/Tokenring/Fast Ethernet/Fast Fiberlink + Fast Ethernet/
Fast Ethernet (BNC, RJ45) Interface with multiprotocol support and SNMP for NOVELL* (IPX) inclusive NDS*, Unix (TCP/IP), Apple EtherTalk/TokenTalk*. Support of the Internet Printing Protocol (IPP).

Your authorised Kyocera Mita distributor:

