

KM-C2230 Specifications

BASIC SPECIFICATIONS

Configuration	Digital Color Copier with Standard 250 Sheet Multi-Purpose Drawer, 500 Sheet Universal Drawer, 150 Sheet Bypass, Standard Network Print, Scan and Internet Fax.
COPY / Scan Resolution	600 x 600 DPI
Print Resolution	600 x 1800 DPI
Copier Memory	Standard 256MB RAM, upgradeable to 512MB / Opt 40GB HDD
Magnification	Full-Size, 4 Reduction / 4 Enlargement, XY Zoom, 3 Custom Zooms, 25 - 400%
Electrical Power Requirements	120V, 60Hz, 15A
Dimensions	27.75"W x 28.75"D x 30.25"H
Weight	247 lbs
Maximum Monthly Volume	100,000 Pages Per Month

OUTPUT SPEEDS

Warm-Up Time	Less than 99 Seconds
First Copy Out (Color / Mono)	12.8 / 6.8 Seconds
Pages Per Minute (Color / Mono)	22 / 35 Letter or Statement, 11 / 18 Ledger
Continuous Copy	Up to 999, Auto Reset to 1

IMAGE QUALITY AND VERSATILITY

Imaging Modes	Text, Photo, Text & Photo, Printed, Map, Copied, Dot Matrix
Additional Features	Multi-Page Enlargement, Gloss Mode, Image Repeat, Mirror Image, Booklet Pagination, Cover Mode, OHP Interleaving, Postcard Mode, Color Separation
Job Management	Job Interrupt, Job List, Job Memory, Job Reserve, Job History, Proof Copy, Priority Job Change, Job Recall, Watermark Page Numbers, Color Adjustments: Auto, Saturation, Portrait, Brightness, Sharpness, Contrast, Hue, Auto / Manual Density, Red, Green, Blue, Color Balance, 20 Monotone Colors, 18 Background Colors, Sample Copy (Test Print), Gradation or Resolution, 998 Account Codes

PUBLISHING

Book Mode	Book Copy, Booklet Pagination, Separation, Spread
Margin Erase	Border, Frame, Edge
Other Features	StoryBoarding: 2in1, 4in1

PAPER SUPPLY

Standard Paper Sources	250 Sheet Multi-Purpose Drawer (up to 12.25" x 18") 500 Sheet Universal Drawer (up to 11" x 17") 150 Sheet Bypass (up to 12.25" x 18")
Min / Max Paper Size	4" x 6" / 12.25" x 18"
Min / Max Paper Capacity	900 / 3,400 Sheets
Paper Weight	16 - 24 lb Bond Universal Paper Drawer or LCD 16 - 40 lb Bond, Up to 140 lb Index*MPD or Bypass
Input Materials	Plain Paper, Transparencies, Labels, Cardstock*, Postcards, Envelopes (Qty: 20 MPD / 10 Bypass; Com10, Monarch)

PAPER HANDLING OPTIONS

DUPLEXING DOCUMENT FEEDER DP-621

Type	Reversing Automatic Document Processor
Acceptable Originals	5.5" x 8.5" / 11" x 17"
Capacity	100 Sheets
Paper Weight	9 lb Bond - 110 lb Index
Dimensions / Weight	23"W x 20.5"D x 5.25"H / 31.25 lbs

AUTOMATIC DUPLEX UNIT DU-621

Paper Size	5.5" x 8.5" / 12.25" x 18"
Paper Weight	16 lb Bond - 110 lb Index
Duplex Modes	1:2, 2:2, 2:1, 2:Book, Book:2
Dimensions / Weight	4.25" W x 17.25"D x 13.5"H / 6.5 lbs

SINGLE POSITION STAPLE FINISHER DF-621

Stack Capacity	Main Tray: 1,000 Sheets, Sub Tray: 250 Sheets, Optional 3rd Tray: 100 Sheets
Paper Size	5.5" x 8.5" / 12.25" x 18"
Paper Weight	16 lb Bond - 140 lb Index
Staple Capacity	30 Sheets: 8.5" x 11", 15 Sheets: 8.5" x 14", 11" x 17"
Edge Staple Position	1 Position
Dimensions / Weight	21.25"W x 25"D x 38.5"H / 84 lbs

MULTI-POSITION STAPLE BOOKLET FINISHER DF-626

Stack Capacity	Main Tray: 1,000 Sheets, Sub Tray: 100 Sheets
Paper Size	5.5" x 8.5" / 12.25" x 18"
Paper Weight	17 lb Bond - 140 lb Index
Staple Capacity	50 Sheets: 8.5" x 11", 25 Sheets: 8.5" x 14", 11" x 17"
Edge Staple Position	3 Positions: Top Left, Left Side, Top Side
Saddle Stitch & Fold	8.5" x 11", 11" x 17"; 20 Books (2-5 Sheets), 10 Books (6-10 Sheets)
Punch	Optional 2 or 3 Hole (PH-620)
Dimensions / Weight	23.75"W x 23.75"D x 36.75"H / 91.75 lbs

UNIVERSAL DRAWER & STORAGE CABINET PF-625

Paper Capacity	500 Sheets
Paper Weight	16 - 24 lb Bond
Paper Size	5.5" x 8.5" - 11" x 17"
Dimensions / Weight	22.5"W x 21.5"D x 10.25"H / 48.5 lbs

DUAL UNIVERSAL DRAWERS PF-627

Paper Capacity	2x 500 Sheets
Paper Weight	16 - 24 lb Bond
Paper Size	5.5" x 8.5" - 11" x 17"
Dimensions / Weight	22.5"W x 21.5"D x 10.25"H / 57 lbs

LARGE CAPACITY DRAWER PF-621

Paper Capacity	2,500 Sheets
Paper Weight	16 - 24 lb Bond
Paper Size	8.5" x 11"
Dimensions / Weight	22.5"W x 21.5"D x 10.25"H / 57 lbs

STANDARD PRINT / SCAN / INTERNET FAX SYSTEM PRINT

Controller	Embedded/350 MHz
Printer Memory	Standard 256MB, upgradeable to 512MB, Optional 40GB Printer HDD
Supported PDL/Emulations	PCL 5c
Fonts	45 PCL, 1 Bitmap
Windows® OS Compatibility	Windows® 98/Me/NT4.0/2000/XP
Novell® OS Compatibility	Novell NetWare® 4.x/5.x/6
Connectivity / Interface	Standard 10/100 BaseTX, Optional Parallel IEEE 1284
Supported Protocols	TCP/IP, LPR, SMB, LPD, Pserver, N Printer, NDPS, HTTP, SMTP, POP3, LDAP, SSL, SNMP
Standard Utilities	Box Utility Software, Printer Management

SCAN

Resolution	200, 300, 400, 600 DPI
Color Mode	Auto Color, Full-Color, GrayScale, Black
Scan Size	8.5" x 11", 8.5" x 14", 11" x 17"
File Formats	PDF, TIFF, JPEG
Supported Protocols	TCP/IP
Scanning Features	Scan to E-Mail, Scan to FTP (Server or Client), Scan to HDD
Standard Utilities	Box Utility
Driver	TWAIN

INTERNET FAX

Resolution	200 x 200 / 200 x 100 DPI
Color Mode	Black
Scan Size	8.5" x 11", 8.5" x 14", 11" x 17"
File Format	TIFF

PRINT OPTIONS

PRINT / SCAN / INTERNET FAX SYSTEM FIERY X3E 22C-KM PRINT

Controller	Embedded Intel Pentium III/ 700 MHz
Printer Memory	Std 128MB RAM (Max 256MB), Std 10GB Printer HDD
Supported PDL/Emulations	Adobe Postscript3, PCL 5c, PCL 6
Fonts	136 Adobe Type 1, 2 Adobe Master, 45 PCL
Windows® OS Compatibility	Windows® 98/Me/NT4.0/2000/XP
Novell® OS Compatibility	Novell NetWare® 4.x/5.x
Mac OS Compatibility	OS 8.6/9.x, 10.x (Classic Mode only), 10.2.4 & above - Native Mode
UNIX OS Compatibility	Sun OS 4.1.x, Solaris 2.5
Connectivity / Interface	Standard 10/100 BaseTX, 10Base5, 10Base2, Parallel, Port 9100, Optional Token Ring
Supported Protocols	TCP/IP, IPX/SPX, LPR, SMB, AppleTalk, HTTP, SNMP, NDPS Gateway, SMTP, POP3/IMAP4, LDAP
Driver	Fiery X3e 22C-KM for Windows, PPD for Mac
Standard Fiery Utilities	WebTools, Downloader, eMail Port, Printer Delete, Spooler, FreeForm2, Netwise, ColorWise Pro Tools, Command Workstation 4.1/LE, Remote Scan
Optional Fiery Utilities	DocBuilderPro 2.0, Graphic Arts Options: (Hot Folders, Auto Trapping, or Spot-on Color), Color Profiler Kit (ES-1000 Spectrometer w/Monitor Profiling Software), Densitometer ED-100

SCAN

Resolution	200, 300, 400, 600 DPI
Color Mode	Auto Color, Full-Color, GrayScale, Black
Scan Size	AutoDetect, Custom, Photo: 3" x 5", 4" x 6", 2.25" x 3.25"
File Formats	PDF, TIFF, JPEG
Supported Protocols	TCP/IP
Scanning Features	Scan to E-Mail, Scan to MailBox, Scan to FTP, Scan to Fiery Hold Queue
Standard Fiery Utilities	Remote Scan
Driver	TWAIN
INTERNET FAX	
Resolution	200 DPI
Color Mode	Black
Scan Size	8.5" x 11", 8.5" x 14", 11" x 17"
File Format	TIFF

* 140lb Index fed from Multi-Purpose Drawer or Bypass Tray loaded with 20 sheets or less.

ADDITIONAL OPTIONS

KM-C2230: 40GB Hard Disk Drive, Parallel Interface, Platen Cover, Mechanical Key Counter, 3rd Tray for DF-621 (JS-621), Desk Storage Drawer (CB-621),
Fiery Options: 128MB RAM Upgrade, Video Interface Kit



Specifications and design are subject to change without notice.
All trademarks and registered trademarks are the property of their respective manufacturers.

Kyocera Mita America, Inc.
225 Sand Road, PO Box 40008,
Fairfield, NJ 07004-0008, USA
©2004 Kyocera Mita America, Inc.
www.kyoceramita.com/us

