



Phaser 7300 Color Printer


peak office performance

When business success is measured in productivity, you want your shared printing resource to be fast. Think of the Phaser 7300 as a hot rod color printer.

Single-pass printing technology, a powerful processor and plenty of memory easily put it at the top of its class.

• 30 ppm color and 37 ppm black sets the highest standard for speed. Your first color page is in the tray in just 16 seconds.

- Busy offices with a variety of print needs will appreciate the power advantage of a 500 MHz processor. Memory is upgradable all the way to 512 MB. And the available hard drive (20 GB minimum) can store frequently printed jobs and optimize job pipelining to make you even more productive.
- Industry-standard true Adobe PostScript 3, PCL5c and advanced print features ensure that all jobs print fast and perfectly every time.



the benefits of Phaser color

Color commands attention and gets better results. With the 7300's versatility, you can enjoy the competitive edge of high-quality color on all of your documents.

- Industry-leading color technologies in the 7300 ensure professional-quality prints. Plus, our exclusive Phaser technology automatically optimizes your print job for the brightest colors, sharpest text and clearest reproduction of scanned images—page by page.
- 2400 dpi makes everyday work look dramatically better. You get crisp, clean text and precise detailing.
- The Phaser 7300 is the single solution for your business printing. It supports more paper sizes and more paper stocks. We've included banner-size pages up to 12 x 36 in. and custom page sizes to expand your options.
- It even compensates for unusual office situations. A paper calibration sensor adjusts print density for unusual paper stocks and environmental conditions, and the unique Run Black feature allows you to choose to print your job "black only" if you run out of a color toner.

reliable and affordable

With the Phaser 7300, you get a feature-packed printer that is easy to install, use and manage—and get it at an affordable, competitive price.

- The Phaser 7300 printer is built to be cost-effective to operate—with a low cost per page—and priced within your budget.
- When you connect the Phaser 7300 to your network, printer installation is literally a one-click process. And printer management is very intuitive for new users while providing a wealth of advanced features for network administrators.
- Xerox office smart know-how is built in. You can check toner levels from your web browser, the dynamic driver interface displays the media loaded in each tray, and PhaserSMART provides a virtual help desk at your fingertips.
- Print large volume jobs in-house and save money. A robust duty cycle of up to 83,000 pages/month ensures plenty of muscle for production printing. And available high-capacity, easy-to-replace toners keep you printing longer at a lower cost.
- Your investment is backed by world-class service and support, a 1-year on-site warranty and the unmatched Xerox Total Satisfaction Guarantee.



time-saving intelligence

When you connect a 7300 to your network, you can take advantage of Xerox CentreWare software. It provides quick and convenient access to a wealth of features, including printer and job status, in-depth accounting information, email alerts, simplified printer installation and network administration.

Dynamic driver interface provides real time printer status. Instant pop-up messages appear on your monitor if any roadblocks arise during your print job, thanks to enhanced PrintingScout. The smart Phaser 7300 printer can even trouble-shoot on its own. It has PhaserSMART, a unique, automated internet-based support system.

Tektronix
COLOR PRINTERS BY

XEROX





Configurations

Performance				
Print speed	up to 30 ppm color / 37 ppm black			
First page out	16 seconds color / 13 seconds black			
Memory (Std / Max)	128 / 512 MB RAM	192 / 512 MB RAM	256 / 512 MB RAM	384 / 512 MB RAM
Processor	500-MHz processor, Adobe PostScript 3 – 136 fonts, PCL5c – 46 fonts			
Internal hard disk	Optional		Standard	
Maximum duty cycle	Up to 83,000 pages/month			
Print Quality				
Maximum resolution	600 x 600 dpi	2400 dpi		
Networking				
Network connectivity	Bi-directional Parallel, USB	10/100Base-TX Ethernet, Bi-directional Parallel, USB		
Paper Handling				
Automatic 2-sided printing	Optional		Standard	
Paper size	4 x 6 in. to 11 x 17 in.	4 x 6 in. to 12 x 18 in.	4 x 6 in. to 12 x 36 in.	
Paper input capability	550-sheet standard tray, 100-sheet multi-purpose tray			
			Additional 550-sheet Feeder	1650-sheet High-Capacity Feeder
Productivity				
Standard features	Smart trays, Run black, Phaser Installer, Intelligent Ready			
		Embedded Web Server, Remote printing, E-mail alerts, Enhanced PrintingScout, PhaserSMART, Job Accounting, Usage Analysis Tool		
			Custom page sizes, Proof/Secure/Saved print JobPipelining with Compression, PDF-direct Booklet printing, Extended font storage	
Warranty	One year on-site, extensive online support, Xerox Total Satisfaction Guarantee			

Media and Supplies

Xerox Phaser Professional Printing Paper

Phaser Premium Color Printing Paper	
500 sheets, 24 lb/90 gsm bond	
A/Letter (8.5 x 11 in)	016-1368-00
A4 (210 x 297 mm)	016-1369-00
11 x 17 in	016-1699-00
A3	016-1700-00
12 x 18 in	016-1900-00
SRA3	016-1901-00

Phaser Premium Cover Paper	
100 sheets, 60 lb/163 gsm cover	
A/Letter (8.5 x 11 in)	016-1823-00
A4 (210 x 297 mm)	016-1824-00

Phaser Premium Business Cards	
25 sheets, 70 lb/190 gsm bond, 10 cards per sheet	
A/Letter (8.5 x 11 in)	016-1898-00
A4 (210 x 297 mm)	016-1899-00

Phaser 35-Series Transparency—Standard	
50 sheets	
A/Letter (8.5 x 11 in)	016-1894-00
A4 (210 x 297 mm)	016-1895-00

Phaser 35-Series Transparency—Premium	
50 sheets, 192gsm bond	
A/Letter (8.5 x 11 in)	016-1896-00
A4 (210 x 297 mm)	016-1897-00

Phaser Color Printing Labels	
100 sheets, 108 lb/176 gsm label	
A/Letter, 30/sheet	016-1812-00
A/Letter, 6/sheet	016-1813-00
A4, 14/sheet	016-1814-00
A4, 8/sheet	016-1815-00

NEW! Phaser CD/DVD Labels and Inserts	
20 sheets, 1 insert/sheet, 10 sheets, 2 labels/sheet	
A/Letter	016-2011-00
A4	016-2026-00

NEW! Phaser CD/DVD Label Applicator	
1 applicator/1 jewel case	016-1885-00

NEW! Phaser Premium Greeting Cards w/ Envelopes	
25 sheets/envelopes, 70 lb/190 gsm	
A/Letter (8.5 x 11 in)	016-1987-00
A4 (210 x 297 mm)	016-1988-00

Consumables

Standard-Capacity Toner Cartridges	
Cyan up to 7,500 pages	016-1973-00
Magenta up to 7,500 pages	016-1974-00
Yellow up to 7,500 pages	016-1975-00
Black up to 7,500 pages	016-1976-00

High-Capacity Toner Cartridges	
Cyan up to 15,000 pages	016-1977-00
Magenta up to 15,000 pages	016-1978-00
Yellow up to 15,000 pages	016-1979-00
Black up to 15,000 pages	016-1980-00

Imaging Units	
Cyan up to 30,000 pages	016-1993-00
Magenta up to 30,000 pages	016-1994-00
Yellow up to 30,000 pages	016-1995-00
Black up to 30,000 pages	016-1996-00
Imaging Unit Kit (includes C, M, Y)	016-1997-00

Additional Supplies	
Fuser (110V) up to 80,000 pages	016-1998-00
Fuser (220V) up to 80,000 pages	016-1999-00
Transfer Unit up to 80,000 pages	016-2000-00

Accessories	
Internal Hard Disk (20GB minimum)	7300HD
Automatic Duplex Unit	7300DPX/A
550 sheet Feeder	7300LTA/A
High-Capacity Feeder, 1650 sheets	7300LTD/A
64 Mbytes Memory	ZMD64/A
128 Mbytes Memory	ZMD128/A
256 Mbytes Memory	ZMD256/A
512 Mbytes Memory	ZMD512/A
Phaser 7300B to 7300N upgrade	7300FNU/A
Capacities for 5% coverage on A-size page	

Specifications

Network/Software

Printer management Xerox CentreWare Printer Management for Microsoft, Novell and Unix, CentreWare IS Embedded Web Server, CentreWare Web Administrator, Xerox NDPGS Gateway, Usage Analysis Tool (not available on non-networked model)

Font capabilities 136 Resident PS fonts and 46 PCL

Printer drivers Windows 95/98/Me, Windows NT 4.x, Windows 2000/XP, MacOS 8/9/X, version 10.1, Novell NetWare 3.x/4.x/5.x/6.x, UNIX (Linux 5.2+, Sun OS 4.x Sun Solaris 2.4+, DEC, HP/UX 11.x, IBM AIX 4.2+, SGI, SCO)

Languages True Adobe® PostScript® 3™, PCL 5c emulation with automatic sensing and switching

Paper handling

Media input trays Standard: 550-sheet standard tray, 100 sheet multi-purpose tray. Optional: 550-sheet feeder (standard on the 7300DT) and 1650 sheet High-Capacity Feeder (standard on the 7300DX)

Media types In all trays: 17-32 lb. (64-120 gsm) bond and 44-60 lb. (120-163 gsm) cover and Phaser transparencies. Automatic 2-sided printing: 20-28 lb. (75-105 gsm) bond. Multi-Purpose Tray: papers up to 75 lb. cover (203 gsm), coated, labels, envelopes, business cards, greeting cards, CD/DVD label/inserts.

Media sizes 7300B: Letter, legal, tabloid, executive, statement, folio, A3, A4, A5, A6, B4 JIS, B5 JIS, ISO B5

7300N/DN: all above sizes plus Tabloid Extra (12 x 18 in.) and SRA3 (320 x 450 mm)

7300DT/DX: all above sizes plus Custom [size range: 4.13-12.6 in. x 5.83-36 in.] including Banner [up to 12 x 36 in.]

Special features

Enhanced PrintingScout instantly displays pop-up Help if attention is needed throughout print job.

Phaser Installer automatically gets you printing in seconds.

PhaserSMART printer diagnostics and troubleshooting via an automated internet-based support system.

Productivity tools: Secure Print*, Proof Print*, Saved Print*, Booklet printing, Negative and mirror images, Scaling, Auto Fit, Watermarks, Custom size paper, Run black, Cover pages, Collation printing*, Remote printing, Separation pages, N-up printing, PDF-direct printing*, Saved Job Repository, MailinX E-mail Alerts (*Requires hard disk)

Color controls

Color standards PANTONE®-approved solid-color simulations, Adobe PostScript device-independent color, CIE international color standards, and support for ICC and Apple ColorSync color management systems

Print quality modes Draft, Standard, Enhanced

Color correction modes Automatic (default), Black & White, sRGB Display, sRGB Vivid, SWOP, Euroscale, Commercial, SNAP, None

Operating

Dimensions width: 26.22 in. (666 mm), height: 18.11 in. (460 mm), depth: 24.65 in. (626 mm), weight: 149 lb. (68 kg)

Environment Temperature: Storage: -4° to 140° F (-20° to 60° C), Operating: 50° to 90° F (10° to 32° C). Relative Humidity: Storage: 10% to 95%, Operating: 10% to 85%. Noise Level: 47 dBA standby, 54 dBA running.

Electrical Model: 110-127 VAC, 50/60 Hz, Consumption: 300 W avg./1000 W max. Model: 220-240 VAC, 50/60 Hz, Consumption: 300 W avg./1000 W max. ENERGY STAR® qualified printer.

Regulatory FCC Part 15, Subpart B, UL listed to UL 1950, CSA Certified to CSA—C22.2 No. 950, CE Mark applicable to directives 73/23/EEC and 89/336/EEC EN 55022

Customer support

1-year On-site Warranty, online web technical support and telephone support. Innovative service offerings include optional extended Service Agreements and custom training for your internal Help Desk. The Phaser 7300 printer is backed by the Xerox Total Satisfaction Guarantee.



Designed for



For the location of your nearest Xerox reseller, or for more information, visit our Web site or call: United States and Canada 1-877-362-6567, other regions see your local Xerox or Fuji/Xerox representative.



XEROX
Worldwide Partner

Copyright © 2004 XEROX CORPORATION. All rights reserved. Contents of this publication may not be reproduced in any form without permission of XEROX CORPORATION. Xerox®, The Document Company®, Phaser®, CentreWare®, and the TetraColor® icon are registered trademarks of XEROX CORPORATION. PhaserSMART®, PhaserMatch™ and the TetraColor™ name are trademarks of XEROX CORPORATION. Total Satisfaction Services™ is a service mark of XEROX CORPORATION. Tektronix® is a registered trademark of Tektronix, Inc. licensed to XEROX CORPORATION. Adobe® and PostScript® are registered trademarks of Adobe Systems Incorporated. ColorSync® is a registered trademark of Apple Computer, Inc. All other trademarks are the property of their respective manufacturers. PANTONE® Colors generated may not match PANTONE-identified standards. Consult current PANTONE Publications for accurate color. PANTONE® and other Pantone, Inc. trademarks are the property of Pantone, Inc. The information in this brochure is subject to change without notice. 11/02, 5/04 730DS-01UC