

LEXMARKTM

OptraTM T616



fast



A space-saving laser printer for high-volume, high-performance and network printing.

- *High-performance printing*
 - Up to 35 pages per minute
 - 200 MHz processor
- *Low cost per page*
 - Ships with a 25,000-page cartridge
- *Expandable output*
 - Add two 5-bin mailboxes, or
 - A high-capacity output stacker and expander
- *Optional convenience copying*
 - OptraImage multifunction attachment



Printer shown with high-capacity output stacker and 2000-sheet drawer.

Lexmark Optra T616

Part Numbers

United States

- Optra T616: 20T4000
- Optra T616n: 20T4040
- Optra T616n (Solaris Ready™): 20T4100

Canada

- Optra T616: 20T4001
- Optra T616n: 20T4041

Technology

- Laser

Speed

- Up to 35 pages per minute
- Less than 13 seconds to first page

Print Quality

- 1200 x 1200 dpi
- 1200 Image Quality
- 600 x 600 dpi with PQET
- 300 x 300 dpi with PQET

Processor

- 200 MHz QED RM 5231

Memory (std/max)

- 16MB/384MB (Optra T616 and Optra T616n)
- Expandable memory options through SDRAM DIMMs
 - 4MB (p/n 5K00013)
 - 8MB (p/n 5K00014)
 - 16MB (p/n 5K00015)
 - 32MB (p/n 5K00016)
 - 64MB (p/n 5K00017)
 - 128MB (p/n 5K00119)
- Hard disk with adapter (p/n 43H5494)
- Flash memory
 - 2MB flash (p/n 5K00115)
 - 4MB flash (p/n 5K00116)
 - 8MB flash (p/n 5K00117)
 - 16MB flash (p/n 5K00118)

Connectivity

- Bidirectional parallel port
- Two Internal Solutions Ports
- On-board 10/100BaseTX Ethernet standard on Optra T616n
- Optional RS-232 serial, RS-422 serial, USB, additional parallel
- Optional LocalTalk®, Coax/Twinax, 10BaseT/2 Ethernet, 10/100BaseTX Ethernet, Token-Ring, infrared

Multifunction Attachments

- OptraImage 222 (p/n 14B5000)
- OptraImage 322 (p/n 14B5025)
- OptraImage 524 (p/n 14B5029)

Compatibility

- PostScript™ 3 emulation standard
- Hewlett-Packard PCL® 6 emulation standard
- PPDS Migration Tool

Font Selection

- PostScript emulation
 - 156 scalable fonts
- PCL 6 emulation
 - 84 scalable fonts
 - 2 bitmapped fonts
- PPDS Migration Tool
 - 39 scalable fonts
 - 5 bitmapped fonts

Paper Handling

- Input (std/max): 1100/4100 pages
 - Maximum input sources: 7
- Output (std/max): 500/3000 pages
 - Maximum output sources: 11
- Media sizes: 2.75" x 5" to 8" x 14" including letter, legal, A4, A5, JIS B5, B4 and executive
 - Optional envelope feeder: DL, C5, B5, 7 3/4, 9, 10
- Media types: plain paper, envelopes, card stock, transparencies, paper labels, vinyl labels, polyester labels, dual web labels
- Media weights: 16-125 lb.

Options

- 250-sheet drawer (p/n 11K0681)
- 500-sheet drawer (p/n 11K0688)
- 250-sheet tray (p/n 11K1059)
- 500-sheet tray (p/n 11K1060)
- 2000-sheet drawer (letter) (p/n 11K0718)
- 2000-sheet drawer (A4) (p/n 11K0719)
- 500-sheet duplex unit (p/n 11K0722)

- 85-envelope feeder (p/n 11K0720)
- 650-sheet output expander (p/n 11K0723)
- 5-bin mailbox (p/n 11K0724)
 - 100 sheets per bin
- 1850-sheet high-capacity output stacker (p/n 11K1440)

Supplies

The Optra T616 ships with

- 25,000-page* Prebate™ print cartridge (p/n 12A5845)

Other supplies

- 10,000-page* Prebate print cartridge (p/n 12A5840)
- 25,000-page* print cartridge (p/n 12A5745)
- 10,000-page* print cartridge (p/n 12A5740)

Operating Systems

- Windows 3.1x, 3.11, 95, 98, NT, 3.51, NT 4.0, Windows for Workgroups 3.1x, MS-DOS, IBM DOS 5.0 or higher, AS/400, OS/2, UNIX, Macintosh® 6.0 or higher
- For a complete, detailed list, please see www.lexmark.com

Size/Weight

- 21.2" H x 16.5" W x 20.2" D (538 mm x 418.1 mm x 513 mm)
- 52 lb. (23.6 kg)

Acoustics

- 53 dBA printing
- 30 dBA idle

Duty Cycle

- Up to 200,000 pages per month maximum

Warranty

- One-year LexOnSite™

*Based on approximately 5% print coverage at comparable industry settings (print darkness=5)

LEXMARK
 Passion for printing ideas.

©1999 Lexmark International, Inc.
 Printed in the United States of America 9/99
 All Rights Reserved
 71K-6101

Lexmark International, Inc. is a global developer, manufacturer and supplier of printing solutions and products, including laser, inkjet and dot matrix printers and associated consumable supplies for the office and home markets. The company is a wholly owned subsidiary of Lexmark International Group, Inc. (NYSE: LXX). Lexmark is on the internet at www.lexmark.com. Specifications subject to change without notice. Lexmark, Lexmark with diamond design, Optra and Prebate are trademarks of Lexmark International Inc., registered in the United States and/or other countries. LexOnSite is a service mark of Lexmark International, Inc. Apple, Macintosh and LocalTalk are trademarks of Apple Computer, Inc., registered in the U.S. and other countries. PCL is a registered trademark of Hewlett-Packard Company. Sun, Sun Microsystems, Solaris and the Solaris Logo are trademarks or registered trademarks of Sun Microsystems, Inc. in the U.S. and other countries, and are used under license. All other trademarks are the properties of their respective owners. As an ENERGY STAR Partner, Lexmark International, Inc. has determined that this product meets the ENERGY STAR guidelines for energy efficiency. ENERGY STAR is a U.S. registered trademark.

